



Q6
POWER CHAIR SERIES

QUANTUM® 6000

FEATURING
MID-WHEEL 6™



QUANTUM® 6000

shown in Metallic Red
with TRU-Balance® Power Tilt
& Recline and Articulating
Leg Rests

The Quantum® 6000 incorporates aggressive new features, powerful 4-pole Hammer motors, and our patent pending Mid-Wheel 6™ design platform to deliver unmatched performance and tight-space manoeuvrability while delivering limitless rehab capability.

Find out more about Quantum® Rehab on the web at www.quantumrehab.com

SPECIFICATIONS

DRIVE WHEELS:	35.5 cm (14") pneumatic
OMNI-CASTERS:	Front: 13 cm (5") solid Rear: 15 cm (6") solid
SUSPENSION:	Active-Trac® ATX Suspension with integrated rear dual-strut suspension and articulating caster beam
MAXIMUM SPEED:	Up to 10 km/ph (6 mph) ¹
BRAKES:	Intelligent Braking (electronic, regenerative disc brakes)
GROUND CLEARANCE:	9 cm (3.5")
TURNING RADIUS:	56 cm (22")
OVERALL SIZE:	Length: 96.5 cm (38") (without footriggings) Width: 65 cm (25.75")
OPTIONAL SEATING:	Synergy® Seat Adjustable Width: 25cm-51cm (10"-20") Adjustable Depth: 25cm-51cm(10"-20") TRU-Balance® Power Positioning System Adjustable Width: 35.5cm-51cm(14"-20") Adjustable Depth: 35.5cm-51cm(14"-20")
DRIVE TRAIN:	Two-motor, mid-wheel drive
BATTERIES:	Two 12 volt, deep cycle Group 24, 75AH
RANGE PER CHARGE:	Up to 40 km (25 miles) ¹
BATTERY CHARGER:	8A, Lester off-board
ELECTRONICS:	100A, PG Remote Plus controller
WEIGHT CAPACITY:	136 kg (300 lbs.) maximum (user weight)
BASE WEIGHT:	71 kg (157.5 lbs.)
BATTERY WEIGHT:	24 kg (53.5 lbs.) (each)
WARRANTY	2-year limited

COLOURS:



¹) Range and speed vary with user weight, terrain type, battery charge, battery condition and tyre pressure.

FEATURES

- Mid-Wheel 6™ allows six wheels on the ground for maximum stability
- Compatible with TRU-Balance® Power Positioning
- OMNI-Casters (nylon, spherical-shaped casters) on front and rear prevent wheel hang-ups
- Side-mounted, easily accessible freewheel levers
- ATX Suspension (Active-Trac® with extra stability) incorporates front OMNI-Casters for enhanced performance over more varied terrain
- 100 amp, PG Remote Plus controller
- Lester 8 amp, off-board charger
- 4-pole Hammer motors
- Accepts (2) Group 24 & (1) NF-22 when used with a vent tray

OPTIONS

- Solid tyres
- Swing-away joystick
- Multi-axis joystick mount
- Elevating leg rests
- Oxygen tank holder
- Neoprene leg rest sleeves
- Gel adductor buttons
- Vent tray
- TRU-Balance® power positioning
- TRU-Balance® power elevating seat
- Angle-adjustable footplates
- Lap belt
- High-mount foot platform
- 70° HD drop-in footrests
- Residual limb supports



"The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice".

"Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement".

21 Healey Rd.
Dandenong, Victoria 3175
www.pridemobility.com

ACN 088 609 661 ABN 66 088 609 661

Tel: 03 9706 4611
Fax: 03 9706 4622

